



270 Birch Bay Lynden Road
Lynden, WA 98264

tel 360.354.1500
888.656.7826
www.oxbocorp.com



Specifications	3216XL	3209XL
Field Dimensions		
Length:	16ft 11in (5.16m)	16ft 11in (5.16m)
Width:	12ft 9in (3.89m)	11ft 6in (3.51m)
Minimum Height:	11ft 9in (3.58m)	11ft 9in (3.58m)
Lift:	24in (0.61m)	24in (0.61m)
Minimum Height with Cab:	13ft 7in (4.14m)	13ft 7in (4.14m)
Weight:	15,700lbs (7,121kg)	14,700lbs (7,121kg)
Weight with Cab:	16,800lbs (7,620kg)	15,800lbs (7,167kg)
Tunnel Dimensions		
Tunnel Width:	4ft 5.5in (1.36m)	5ft 4in (1.63m)
Minimum Tunnel Height:	6ft 6in (1.98m)	6ft 6in (1.98m)
Maximum Tunnel Height:	8ft 6in (2.59m)	8ft 6in (2.59m)
Tires		
Front size:	16.5 x 16	
Standard Rear Tires:	16.9 x 26	
Engine		
Engine:	Tier III, 100hp turbo charged John Deere 4045T	
Other Specifications		
Transmission:	Sauer 46cc	
Final Drives:	Fairfield W5 rear	
Hydraulics:	Sauer 75cc pump	



3200 series



wide-trellis grape harvesters



3216XL & 3209XL

Oxbo continues the legacy of the Korvan brand by offering superior grape harvesters backed by local parts and service support. Growers continue to trust the wide-trellis 3200 Series to set the standard in various vineyard configurations.

The 3200 Series now offers extended catching area in both the 3209XL and the 3216XL. This added catching area has proven to deliver more productivity by allowing you to increase your harvesting speed in high tonnage crops. Oxbo continues to improve the 3200 series to deliver dependable performance in all field conditions.

backed by support

Oxbo backs the model 3000 series with over 50 years of experience designing, engineering, building, and supporting niche market harvesting solutions. Oxbo stands behind every harvester with readily available parts and in-field service support.

designed for you field conditions

Designed and built in the USA to the highest manufacturing standards, the Oxbo 3200 Series delivers reliable performance no matter which model you choose.

The Oxbo 3209XL is the only machine on the market designed to efficiently and effectively pick GDC. It features a unique tilting bow rod head, capable of tilting 28° and a 64-inch wide picking tunnel to accommodate 48-inch GDC as well as single curtain; change over between head configurations is fast and easy.

The Oxbo 3216XL offers a heavy duty chassis capable of high quality fruit, even in high tonnages. The 3216XL chassis is also easily configured to offer the most trusted platform for continuous tray raisin harvesting. High capacity buckets carry, not drag, your fruit for a clean end product.

Center mount cab: Optional comfortable, heated and air conditioned cab is center mounted for optimal visibility in all harvesting conditions

High quality fruit: The Oxbo 3200 Series consistently delivers high quality wine and juice grapes

Three fan cleaning system: Proven effective at removing debris by removing M.O.G. at a slight fruit transition

Low mounted engine: 100hp John Deere, Tier III engine delivers easy maintenance, excellent stability, as well as economical, clean, and reliable performance



Bucket conveyance system: Durable buckets gently carry your fruit, no drag it, to deliver more clean, whole fruit

Features

- **Bucket conveyance:** High quality material for long life and to maintain fruit quality
- **NEW Improved bow rod system** Reduces maintenance and improves consistency in the picking performance
- **Hydraulically adjustable tilting picking system:** Delivers the flexibility to pick many trellis types. The 3209XL can pick 48-inch GDC.



- **Heavy duty harvesters:** The Oxbo 3000 has been designed and has proven to deliver long lasting field performance for thousands of harvest hours

Options

- Air conditioned
- Traction torque hub package
- Rear flotation tires
- Break steer system
- Posi-traction
- Reversing buckets
- Rear catwalk (3216XL only)
- Rear ladder (3216XL only)
- Recycle bin (3216XL only)
- Nylon catcher plates
- Bucket reverse
- **NEW** High torque trash removers
- Remote greasing
- Steering light system
- Fluorescent lights

